MV 250 J ASA Series



Application

- Decoration of supply and exhaust vents of public, residential and industrial ventilation systems.
- External wall mounting.

Design

- Made of quality and durable plastic.
- Multi-element structure.
- Fitted with louvre shutters for back flow prevention.
- Screw fixing.

Colour modifications







Modifications

MV 250/150 VJ ASA, MV 250/200 VJ ASA - models with a round flange and louvre shutters



- Fitted with a round connecting flange for mounting with Ø 150 mm (MV 250/150 VJ ASA) or Ø 200 mm (MV 250/200 VJ ASA) air ducts.
- Fitted with louvre shutters for back flow prevention.



MV 250 VJD ASA - model with four-element flange and louvre shutters




- Equipped with four-element connecting flange with adjustable diameter for connection to Ø 100-150 mm round air duct.
- Fitted with louvre shutters.




Overall dimensions

Model	Dimensions, [mm]						
	□В	□H	D	L	L1	Air pass, [m²]	Fig. no.
MV 250 VJD ASA	250	214	100-150	15	41	0,0177-0,056	1, 2
MV 250/150 VJ ASA	250	214	150	15	41	0,0177-0,056	1, 3
MV 250/200 VI ASA	250	214	200	15	41	0.0177-0.056	1 4










Fig. 1 Fig. 2

Fig. 3

Fig. 4